

Boot-wash stations

PRODUCT GUIDE · EQUIPMENT-02

Boot-wash stations help remove contamination or debris from footwear at a designated entry or exit point.

Application

Treatment facilities, washdown areas and controlled access points.

Stoddart WT.BWS reference specifications

Reference series	SPPL.WT.BWS.01 and SPPL.WT.BWS.02 boot-wash stations
Construction	1.5 mm grade 304 stainless steel; No. 4 satin finish
Model .01 dimensions	408 L × 750 D × 915 H mm
Model .02 dimensions	650 L × 750 D × 915 H mm
Water connection	Single 15 mm (½ in BSP) cold or tempered supply
Waste connection	40 mm
Washing equipment	Angled brushes plus supplied wall tap, hose and hand nozzle
Solids collection	Front-access collection basket
Fixing	Height-adjustable feet suitable for fixing to ground

Reference configuration only. Dimensions and ratings apply to the named model; confirm the supplied configuration and suitability with your quote.

Details to include in your enquiry

Users and expected contamination · Water supply and drainage · Footprint, material and cleaning requirements

Technical references

[Stoddart WT.BWS reference specifications — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

[Stoddart WT.BWS datasheet, revision 10 May 2024 — open reference](#) · Product data sheet · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.