Washdown spray guns

PRODUCT GUIDE · EQUIPMENT-09

Washdown spray guns control the delivery pattern and flow of compatible cleaning water.

Application

Equipment cleaning and general industrial washdown.

Dixon DWG050A reference specifications

Reference model	DWG050A Flow Boss heavy-duty washdown gun
Construction	Stainless steel and brass with blue rubber cover
Inlet	½ in female BSP
Maximum operating pressure	2400 kPa (350 psi)
Maximum temperature	80°C
Flow capacity	57 L/min at 500 kPa (72 psi)
Spray pattern	Hollow cone
Connection position	Hose attaches at base of handle

Reference configuration only. Ratings apply to Dixon DWG050A; confirm hose, inlet fittings and water duty as an assembly. Not for steam lines.

Details to include in your enquiry

Water pressure, flow and temperature · Inlet size and thread · Cleaning agents and handling requirements

Technical references

Dixon Australia DWG050A product specification — open reference · Manufacturer / supplier reference · Confirm current revision with quotation

Dixon industrial products catalogue: washdown service and steam exclusion — open reference · Catalogue · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.