

Lockout padlocks and hasps

PRODUCT GUIDE · EQUIPMENT-28

Lockout padlocks and hasps support a specified isolation procedure by securing compatible lockout points.

Application

Site maintenance isolation systems and group lockout arrangements.

Master Lock 410RED and 420 reference specifications

Reference products	410RED safety padlock and 420 group-lockout hasp
Padlock body	Red Zenex thermoplastic, 38 mm wide
Padlock shackle	Metal; 38 mm long × 20 mm inside width; 6 mm diameter
Keying	410RED is keyed different; key-retaining cylinder
Hasp construction	Heavy-gauge steel jaws; red vinyl-coated handle
Hasp dimensions	44 × 114 mm; 25 mm internal jaw diameter
Hasp capacity	Up to six safety padlocks

Reference configuration only. Dimensions and ratings apply to the named model; confirm the supplied configuration and suitability with your quote. Select keying and lockout geometry against the approved site isolation procedure.

Details to include in your enquiry

Site isolation procedure and lockout point · Shackle clearance, hasp size and required quantity · Keying, identification and material requirements

Technical references

[Master Lock 410RED and 420 reference specifications — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

[Master Lock 420 steel lockout hasp — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.