

Hydraulic tipper trailers

PRODUCT GUIDE · EQUIPMENT-38

Hydraulic tipper trailers for suitable loose materials and site loads.

Application

Transporting and tipping compatible materials within the configured trailer limits.

Hydraulic tipper trailers — reference specifications

Reference product	Ox Trailers Pro Series rear hydraulic tipper trailer range
Aggregate trailer mass (ATM) options	3,500 or 4,500 kg
Published tare — 3,000 × 2,100 mm / 3.5 t configuration	1,390 kg
Tray length options	3,000 / 3,600 / 4,200 mm
Overall trailer width options	2,100 or 2,400 mm
Dropside height	250 mm
Hydraulic tipping system	6-stage telescopic ram with 12 V power pack

Photograph represents the manufacturer's rear-tipper range. Listed sizes and ATM values are options; the stated tare applies only to the labelled configuration. Confirm the selected configuration and certified payload.

Details to include in your enquiry

Material volume and load mass · Body dimensions and tipping arrangement · Towing brake and delivery requirements

Technical references

[Reference product information — open reference](#) · Catalogue · Confirm current revision with quotation

[Ox Trailers Tipper Trailer Catalogue — specifications on page 6 — open reference](#) · Catalogue · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.