

Jackhammers and demolition breakers

PRODUCT GUIDE · EQUIPMENT-44

Demolition breakers for compatible concrete, masonry and surface-removal tasks.

Application

Breaking and demolition with the appropriate bit and selected tool.

Jackhammers and demolition breakers — reference specifications

Reference product	Makita HM1812 28.6 mm hex-shank electric demolition breaker
Model	HM1812
Power source	Corded electric
Continuous input	2,000 W
Net weight	31.3 kg
Impact energy	72.8 J
Impact rate	870 blows/min
Tool holder	28.6 mm hex shank
Overall length	843 mm
Power cord	5 m

Manufacturer specifications refer to the identified model. Confirm Australian supply voltage, plug, chisel compatibility and supplied accessories before ordering.

Details to include in your enquiry

Material and duty · Power source and bit holder · Required chisels and quantity

Technical references

[Reference product information — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

[HM1812 product sheet — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

[HM1802/HM1812 user manual — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.