

# Ball-and-socket lever couplings

PRODUCT GUIDE · FITTINGS-02

Ball-and-socket lever couplings form a removable connection using a shaped male end, a sealing ring and a lever clamp.

## Application

Temporary pumping, dewatering and suitable suction or discharge lines.

## Type B ball-and-socket reference

|                |                                                         |
|----------------|---------------------------------------------------------|
| Material       | Hot-dip galvanised steel                                |
| Assembly       | Male spigot, female socket, lever ring and sealing ring |
| Separate parts | Flanged tails, weld-on ends and replacement seals       |

Reference configuration only. Dimensions and ratings apply to this documented series; the offered item is confirmed with your quote.

| Nominal size — mm | Inch size |
|-------------------|-----------|
| 50                | 2         |
| 80                | 3         |
| 100               | 4         |
| 125               | 5         |
| 150               | 6         |
| 200               | 8         |

## Details to include in your enquiry

Exact mating profile and measured size · Seal material and fluid · Pressure, vacuum and expected pipe movement

## Technical references

[Coupling sizes and assembly parts — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.