

PVC-U socket tees

PRODUCT GUIDE · FITTINGS-29

Three-way PVC-U socket fittings for branching a compatible solvent-jointed pipe system.

Application

Specified pressure pipework, plant service lines and compatible PVC-U branch connections.

Schedule 80 PVC-U · equal socket tee

Material	PVC-U
Dimensional system	Imperial IPS, Schedule 80
Joint	Solvent-weld sockets
Fitting standard	ASTM D2467

Lettered dimensions refer to the linked supplier drawing. DN is nominal, not socket bore. Values are for this IPS series; do not substitute metric fittings.

DN	Inch size	L — mm	H — mm	G — mm
15	½	75	38	16
20	¾	88	44	18
25	1	102	51	22
32	1¼	116	58	26
40	1½	124	62	27
50	2	147	74	34
65	2½	177	89	43
80	3	191	96	47
100	4	239	120	62
150	6	359	180	103
200	8	447	224	121

Details to include in your enquiry

Main and branch pipe sizes · Pipe dimensional system and service duty · Fluid, temperature and jointing-system requirements

Technical references

[Dimension table and labelled drawing — open reference](#) · Drawing / dimensions · Confirm current revision with quotation

Selected source fields compared 2026-10-05. All 11 displayed equal-tee L/H/G rows agree with the source table.

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.