

Spill absorbent pads and socks

PRODUCT GUIDE · MISC-09

Absorbent pads and socks provide replaceable materials for a spill-response kit selected for the expected liquid.

Application

Specified spill-kit replenishment and suitable maintenance clean-up tasks.

Spill Station oil/fuel pads and socks — reference specifications

Pad reference	PAD203/100
Pad dimensions	480 × 430 mm
Pad basis weight	400 g/m ²
Pad material	Polypropylene microfibres with spunbond coverstock
Pad absorbency	Up to 1.4 litres per pad
Pad pack	100 pads
Sock / mini-boom reference	WMB12100
Sock dimensions	1200 × 75 mm
Sock supply	Each; white
Service type	Oil and fuel / hydrocarbon spills

These reference products are the oil/fuel type. Select general-purpose or chemical absorbents separately for the actual liquid; the pad capacity is a supplier maximum.

Details to include in your enquiry

Expected liquid and spill-kit type · Pad or sock dimensions and required quantity · Compatibility, capacity and disposal requirements

Technical references

[Spill Station PAD203/100 — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

[Spill Station WMB12100 — open reference](#) · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.