Drain and toilet plungers

PRODUCT GUIDE · MISC-16

Hand-operated plungers use a sealed cup to move water and help clear local sink, basin or toilet blockages.

Application

Routine drain maintenance where the cup shape can seal against the fixture outlet.

Plunger types and identified reference dimensions

Cup reference	Haron H120: 100 mm cup; 265 mm overall length
Toilet-flange reference	Korky 92-4 / 92-8A: 6-inch cup; 18-inch handle
Korky head	Non-marking rubber
Korky handle	Straight plastic handle
Bellows reference	Haron HP06 Easy Grip Master
Haron HP06 end cone	Rubber; two positions for basins or toilets
Haron HP06 feature	Air-relief valve

Dimensions refer to the individual products. Show the three original photographs as a gallery; image display sizes are not a common-scale comparison.

Details to include in your enquiry

Plunger type and fixture · Cup diameter and handle length · Individual type or mixed quantity

Technical references

Haron H120 — open reference · Manufacturer / supplier reference · Confirm current revision with quotation

Korky 92-4 / 92-8A — open reference · Manufacturer / supplier reference · Confirm current revision with quotation

Haron HP06 — open reference · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.