Silicone tubing

PRODUCT GUIDE · PIPING-26

Flexible silicone tubing for applications that call for a specific silicone grade, bore and wall thickness.

Application

Compatible transfer lines, equipment connections and specified small-bore tubing replacements.

Tasmanian Hose Solutions SIL silicone tube reference

Material	Silicone
Construction	Non-reinforced; smooth internal bore
Listed dimension pair example	12 × 8 mm
Length for 12 × 8 mm option	10 m
Operating temperature	−60 to +200 °C
Duty	Open-ended, gravity-fed or low-pressure transfer
Resistance	UV and ozone resistant

Reference model/family only. These published dimensions and limits do not apply to every product in this category; confirm the supplied configuration with the quotation. The source lists dimension pairs without explicit OD/ID labels; confirm the ordered bore and outside diameter. No numeric pressure rating is stated.

Details to include in your enquiry

Fluid and temperature range · Bore, outside diameter and supplied length · Pressure or vacuum duty and required grade

Technical references

Tasmanian Hose Solutions — food-grade silicone tubing — open reference · Manufacturer / supplier reference · Confirm current revision with quotation

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.