

# Pipe repair clamps

PRODUCT GUIDE · VALVES-22

Pipe repair clamps seal a local pipe defect using a surrounding clamp body and gasket.

## Application

Maintenance of suitable water and process pipework.

## Rapid CR1 / CR2 / CR3 — pipe repair clamp series

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| Pipe outside-diameter range | 40–2,000 mm across the series                 |
| Clamp lengths               | 150–600 mm                                    |
| Shell                       | 316 stainless steel, 2B finish                |
| Lugs and receiver bars      | 316 stainless steel; welded and passivated    |
| Bolts, nuts and washers     | 316 stainless steel                           |
| Bolt treatment              | Rolled threads with anti-galling coating      |
| Standard gasket             | Nitrile rubber for water, gas and oil service |
| Gasket option               | Natural rubber on request                     |
| Armour                      | 316 stainless steel, vulcanised into gasket   |

Reference configuration only. Specifications apply to the named supplier series or model; the offered item and suitability are confirmed with the quotation. Select by actual pipe outside diameter and defect dimensions. Pressure capability is not inferred from nominal pipe size.

## Details to include in your enquiry

Actual pipe outside diameter · Pipe material and defect dimensions · Pressure, fluid and accessibility

## Technical references

[Rapid Clamps CR series product data — open reference](#) · [Manufacturer / supplier reference](#) · [Confirm current revision with quotation](#)

Reference values apply only to the identified configuration. The offered model, dimensions, approvals and lead time are confirmed with your quote. Availability is subject to confirmation.